

5252M Solvent Cleaner

Product Description

Kester 5252M is a halogen-free solvent developed for cleaning applications. Kester 5252M is not ozone depleting and is environmentally friendly. It is a suitable substitute for chlorinated solvents used in cleaning applications where fast air-drying is critical.

Kester 5252M can be used as a solvent to clean stencils efficiently. When there is a possibility of current leakage when parts or assemblies are to be painted or encapsulated, when flux impedes the operation of a mechanical devices, and when cleanliness is important. Kester 5252M provides rapid, effective and safe cleaning action. This cleaning solvent is a non-ionic and relatively nontoxic liquid with mild odor.

Performance Characteristics:

- O.D.P. value of 0, complying to the Montreal Protocol regulations
- Non-ionic and non-corrosive
- Mild odor
- Non-carcinogenic and relatively non-toxic
- Good cleaning efficiency

Physical Properties

Specific Gravity: 0.790 ± 0.005 Anton Paar DMA 35 @ 25°C

Application Notes

Kester 5252M is applied to the part to be cleaned either by immersion or similar means, in such as a manner that the residue is completely immersed in the solvent. When the residue has completely dissolved and is no longer visible, the residual solution is rinsed off with more solvent. It can be used with cleaning equipment such as ultrasonic machines to clean the stencils.

If immersion washing is employed, the liquid should be replaced at regular intervals in order to avoid solvent contamination. Successive rinse tanks can be employed using a second or even a third dip in clean solvent. The purpose is not to only dissolve the residue but also to remove it after it is dissolved.

Cleaning:

Besides being as an effective cleaning solvent for stencils, Kester 5252M can also be used as a rosin residue remover. Kester 5252M readily dissolves reflowed solder pastes, and wave-soldered flux residues. It is a more effective cleaner than is propanol and other commonly used solvents.

The performance of Kester 5252M is confirmed on removing the residues from the following products: -

<u>R244</u>	R24	<u>4T R2</u>	<u>253</u>	<u>R253-5</u>	<u>R289TM</u>	<u>FL250</u>	FL25	<u>60H</u>	
***	***	* *	**	***	***	***	***	***	
	22	022.7	054	-BN 9:	51-S	055	49500		
	<u>33</u> ***	<u>933-7</u> ***			***	<u>955</u> ***	<u>1850S</u> ***		

*-degree of cleanliness (*** for excellent cleanliness)

Storage and Shelf Life:

Kester 5252M is flammable. Store away from sources of ignition. Shelf life is 2 years from date of manufacture when handled properly and held at 10-25°C (50-77°F).

Health & Safety:

This product, during handling or use, may be hazardous to health or the environment. Read the Material Safety Data Sheet and warning label before using this product.

World Headquarters: 515 E. Touhy Avenue. Des Plaines, Illinois, 60018 USA Phone: (+1) 847-297-1600 • Email: customerservice@kester.com • Website: www.kester.com

Asia Pacific Headquarters 500 Chai Chee Lane Singapore 469024 (+65) 6449-1133 customerservice@kester.com.sg European Headquarters Ganghoferstrasse 45 D-82216 Gernlinden Germany (+49) 8142-47850 customerservice@kester-eu.com Japanese Headquarters 20-11 Yokokawa 2-Chome Sumida-Ku Tokyo 130 Japan (+81) 3-3624-5351 jpsales@kester.com.sg

The data recommendations presented are based on tests, which we considered reliable. Because Kester has no control over the conditions of use, we disclaim any responsibility connected with the use of any of our products or the information presented. We advise that all chemical products are be used only by or under the direction of technically qualified personnel who are aware of the potential hazards involved and the necessity for reasonable care in their handling. The technical information contained herein is consistent with the properties of this material but should not be used in the preparation of specification as it is intended for reference only. For assistance in preparing specifications, please contact your local Kester office for details.